

Technical Data Sheet
**Clima Redboard
Window Soffit Board**



[Clima Redboard Laibungsplatte]

**interior pre-primed mineral window soffit board
made of calcium silicate**

Areas of application:

- for use in areas around windows and door reveals and door reveals in interior spaces
- to compensate for thermal bridging
- prevents mould growth
- absorbs excess interior air humidity

Features/benefits:

- primed on the room side (sanded on both sides)
- controls humidity
- capillary-active
- breathable
- heat-insulating
- mould-resistant
- non-flammable (A1)
- countless micropores
- natural raw materials
- environmentally friendly
- 'Made in Germany' quality

Technical data:

- Material: Calcium silicate, cellulose fibres
- Fire behaviour: Class A1 in accordance with EN 13501-1:2010 (in keeping with ETA-19/0559)
- Water vapour resistance factor: $\mu = 3$
- Thermal conductivity: $\lambda_D (23.50) = 0.059 \text{ W/(mK)}$
 $\lambda_{\text{Rated value}} = 0.062 \text{ W/(mK)}$
(in keeping with ETA-19/0559)
- Apparent density range: 180-187 kg/m³
- Pressure resistance: $\geq 1000 \text{ kPa}$
- Water absorption coefficient: 46 kg/m²√h
- Water saturation: 920 kg/m³
- pH value: approx. 10
- Environmental product declaration: EPD-CSP-20180010-IBC1-DE

The technical information and instructions for use contained in this document are correct to the best of our knowledge and are provided in good faith. The content of this document does not constitute an explicit or implicit guarantee for the performance of these products. As we have no control over how our materials will be used or the conditions under which they are used, we can only guarantee that these products meet our quality standards. We can therefore only guarantee the quality of our products within the framework of our General Terms and Conditions, but we cannot guarantee their successful functioning in every situation. Subject to changes without prior notice. This data sheet replaces all previous data sheets.

Technical Data Sheet

Clima Redboard Window Soffit Board



[Clima Redboard Laibungsplatte]

Instructions for use:

The **Clima Redboard Window Soffit Board [Clima Redboard Laibungsplatte]** corresponds to **Clima Redboard pro** in terms of its structure and design. Thus, the same processing guidelines and specifications generally apply to substrate preparation and surface coating.

In general, **Clima Redboard Window Soffit Boards [Clima Redboard Laibungsplatten]** are glued without cavities and glued over the entire surface. The application of the adhesive (**System Adhesive [Systemkleber]** or, in the case of substrates containing gypsum: **Special Adhesive SB [Spezialkleber SB]**) is applied following the comb bed method using a notched trowel (min. 10 mm). Uneven substrates should be levelled in advance using mineral **Patching Plaster [Ausgleichsputz]** from redstone.

Suitable substrates are, for example, load-bearing and levelled lime or lime-cement plasters. Mineral substrates may be damp, but not wet. Wallpaper, paints, loose components and filler layers containing plaster must be removed. For dry gypsum plasters with a thickness of > 10 mm, **Special Adhesive SB [Spezialkleber SB]** should be used.

Mould infestations must be removed professionally. If it is necessary to disinfect the substrate, redstone **Mould and Spore Destroyer SuS [Schimmelpilz- und Sporenvernichter SuS]** from the Vivo Mould Remedy line ["Schimmelsanierung (Vivo)"] should be used. Building defects and penetrating moisture such as rising damp or driving rain must be remedied with appropriate measures. Absorbent substrates must be pre-wetted or prepared with redstone **Primer [Grundierung]**.

Clima Redboard Window Soffit Boards [Clima Redboard Laibungsplatten] are placed, for example, in the area around the window on the front side of the frame. To prevent cracks, it is recommended to insert redstone **Pre-Compressed Sealant Tape [Komprimierband]** into the connection joint. Decoupling to further adjacent building components such as floors and ceilings using redstone **Pre-Compressed Sealant Tape [Komprimierband]** is to be provided for.

In addition, corrosion-free corner protection rails (e.g. made from plastic or aluminium) should be used, which are fixed using **System Adhesive [Systemkleber]** or **Special Adhesive SB [Spezialkleber SB]** and, if necessary, non-rusting fasteners. Arched and vaulted reveals can be adapted using smaller segment strips and oblique sections.

Dimensions / Form of delivery / Article No.:

250 x 500 x 15 mm / 20 pcs. per package / RBL15250MM

Other:

The requirements of the EC Safety Data Sheet must be adhered to.

The technical information and instructions for use contained in this document are correct to the best of our knowledge and are provided in good faith. The content of this document does not constitute an explicit or implicit guarantee for the performance of these products. As we have no control over how our materials will be used or the conditions under which they are used, we can only guarantee that these products meet our quality standards. We can therefore only guarantee the quality of our products within the framework of our General Terms and Conditions, but we cannot guarantee their successful functioning in every situation. Subject to changes without prior notice. This data sheet replaces all previous data sheets.