

Technical Data Sheet
Secco Primer FS
[Secco Grundierung FS]



Salt-blocking primer for
Secco Barrier Plaster [Secco Sperrputz] and
Secco Base and Dehumidifying Plaster
[Secco Sockel- und Entfeuchtungsputz]

Areas of application:

- for the pre-treatment of mineral substrates
- Salt barrier under **Secco Barrier Plaster [Secco Sperrputz]** and **Secco Base and Dehumidifying Plaster [Secco Sockel- und Entfeuchtungsputz]**

Characteristics:

- strengthening, salt blocking, pre-sealing effect
- water vapour permeable
- solvent-free
- highly alkaline

Technical data:

- Thickness: approx. 1.2 g/cm³
- pH value: approx. 11.5
- Wall strengthening capability: < 5% N/mm²
- water vapour permeability: > 90%
- Use: approx. 500-750 ml/m² (depending on substrate)
- Working temperature: at least 8°C

Instructions for use:

To avoid staining or discolouration, carefully cover or mask window sills, glass, ceramics, stone and metal surfaces before starting to work with **Secco Primer FS [Secco Grundierung FS]**. Immediately remove any splashes with water.

The mineral substrate must be solid, adhesive and load-bearing and free from contamination (paints, coatings, oil, sintered layers, etc.). Old plasters should be removed down to masonry level at least 80 cm beyond visible damage and efflorescence. Loose jointing mortar must be removed in advance. Open joints and uneven sections must be repaired in advance using **Secco Barrier Plaster [Secco Sperrputz]** or **Secco Base and Dehumidifying Plaster [Secco Sockel- und Entfeuchtungsputz]**. Dry and absorbent substrates must be adequately pre-wetted before applying **Secco Primer FS [Secco Grundierung FS]**.

Spray the **Secco Primer FS [Secco Grundierung FS]** onto the pre-wetted, adhesive and load-bearing substrate or apply with a brush or roller (pre-wet smooth substrates, apply **Secco Quick Rough Plaster [Secco Spritzbewurf schnell]**, pre-wet again after sufficient hardening and treat with **Secco Primer FS [Secco Grundierung FS]**).

The technical information and instructions for use contained in this document are correct to the best of our knowledge and are provided in good faith. The content of this document does not constitute an explicit or implicit guarantee for the performance of these products. Since we have no control over how our materials will be used or the conditions under which they are used, we can only guarantee that these products meet our quality standards. We can therefore only guarantee the quality of our products within the framework of our General Terms and Conditions, but we cannot guarantee their successful functioning in every situation. Subject to changes without prior notice. This data sheet replaces all previous data sheets.

Technical Data Sheet
Secco Primer FS
[Secco Grundierung FS]



Important: Apply the subsequent plaster within 10-20 minutes after priming (fresh in fresh). If allowed to dry for longer, the plaster adhesion worsens.

Cleaning:

Clean equipment with water immediately after finishing work.

Storage:

Keep cool and dry and protect from heat and frost in sealed original containers for at least 1 year.

Dimensions/Form of delivery/Article No.:

5 l canister; FS05GFS

10 l canister; FS10GFS

Other:

The requirements of the EC Safety Data Sheet must be adhered to.

The technical information and instructions for use contained in this document are correct to the best of our knowledge and are provided in good faith. The content of this document does not constitute an explicit or implicit guarantee for the performance of these products. Since we have no control over how our materials will be used or the conditions under which they are used, we can only guarantee that these products meet our quality standards. We can therefore only guarantee the quality of our products within the framework of our General Terms and Conditions, but we cannot guarantee their successful functioning in every situation. Subject to changes without prior notice. This data sheet replaces all previous data sheets.